
PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number: WO 97/13465
A61B 17/04	A1	(43) International Publication Date: 17 April 1997 (17.04.97)
(21) International Application Number: PCT/SE (22) International Filing Date: 8 October 1996 (BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
(30) Priority Data: 9503512-7 9 October 1995 (09.10.95) (71) Applicant (for all designated States except US): MEI MEDICAL AB [SE/SE]; P.O. Box 20047, S-200 7 (SE).	DSCAN	Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.
(72) Inventor; and (75) Inventor/Applicant (for US only): ULMSTEN, Ulf Ridvägen 18 D, S-182 35 Danderyd (SE).	[SE/SI):
(74) Agents: STRÖM, Tore et al.; Ström & Gulliksson Box 4188, S-203 13 Malmö (SE).	AB, P.).
•		
(54) Title: SURGICAL INSTRUMENT FOR TREATING	G FEM.	LE URINARY INCONTINENCE
(57) Abstract		·
A surgical instrument for treating female urinary income a shank (10) having a handle (11) at one end thereof, and to like elements (21A, 21B) which can be connected one at shank at the other end thereof to form a curved end portion are attached at one end thereof each with one end of a neintended to be implanted into the body and is covered by a (34).	two cur the tine on of the tting (2)	ed needle- e with the shank and) which is



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	· GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	
CN	China	LR	Liberia	SZ	Senegal Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Swaziiang Chad
CZ	Czech Republic	ເບ	Luxembourg	TG	
DE	Germany	LV	Latvia		Togo
DK	Denmark	MC	Monaco	TJ	Tajikistan
EE	Estonia	MD		TT	Trinidad and Tobago
ES	Spain	MG	Republic of Moldova Madagascar	UA	Ukraine
FI	Finland	ML	Mali	ບຣ	Uganda
FR	France	MN		US	United States of America
GA	Gabon	MR	Mongolia	UZ	Uzbekistan
3/4	UBUUM.	MK	Mauritania	VN	Viet Nam

WO 97/13465 PCT/SE96/01269

Surgical instrument for treating female urinary incontinence

5

30

35

The invention relates to a surgical instrument for treating female urinary incontinence, of the type described in PCT/SE95/00964 the content of which is incorporated herein by reference, comprising a shank having a handle at one end thereof, and two curved needle-like elements which are each attached at one end thereof to one end of a tape to be implanted into the body, and are constructed to be connected one at the time with the shank to form a curved portion at the other end thereof each element being intended to be passed into the body via the anterior (suburethral) vaginal wall and being dimensioned to extend from the inside surface of the vaginal wall over the back of the pubic bone to the outside of the abdominal wall.

The object of the invention is to further improve the surgical instrument disclosed in said document and for this purpose the instrument of the invention has obtained the characterizing features of claim 1.

The invention will be explained in more detail with reference to the accompanying drawings which disclose the surgical instrument according to the invention and wherein.

FIG. 1 is a side view of the surgical instrument according to the invention,

FIG. 2 is a plan view of the surgical instrument,

FIG. 3 is an exploded side view of one of the needles and tape and shrinkage hose to be connected with said needle,

FIG. 4 is a side view of the needle in FIG. 3 with the tape connected therewith,

FIG. 5 is an enlarged fragmentary axial cross sectional view of a coupling of the instrument for connecting an exchangeable needle thereof, and

FIG 6 is a side view of two needles and a tape interconnecting said needles.

In the following description the same reference numerals have been used as in PCT/SE85/00964 for corresponding details of the instrument.

The surgical instrument comprises a cylindrical tubular shank 10 having at one end thereof a handle 11. At the other end of the shank there is a socket 14. A cylindrical shaft 15 is rotatably mounted in the shank and can be rotated manually by means of a knob 16 mounted to one end of the shaft. The other end of the shaft forms a cylindrical portion 17, FIG 5, of smaller outside diameter than the shaft, which joins a portion 18 having external threads, a smooth end portion 19 of further reduced diameter joining the threaded portion 18, end portion 19 forming a guide pin at said other end of the shaft. Portions 18 and 19 are received in the portion of socket 14 projecting from the shank. The surgical instrument as described so far is in agreement with the instrument disclosed in PCT/SE95/00964 except that the end portion 14' of socket 14 is flattened from opposite sides (cfr FIGS 1 and 2), so that the cross section of said end portion is noncircular.

20

25

30

The surgical instrument also includes an exchangeable and disposable needle 21 which at one end thereof is attached to the shank at one end of the needle and extends over substantially a quarter of a circle to the other, free end thereof in order to follow substantially the profile of the pubis between the vagina and the abdominal wall. The needle has uniform circular cross section and has a smooth, preferably polished outside surface. At the free end thereof the needle forms a point 22 by being terminated by a conical portion.

For attachment of needle 21 to shank 10 the needle forms at said one end thereof a straight portion 30 which

is cylindrical but has milled flat faces 31 over that part of said portion 30, extending from the adjacent end of the needle, which shall be received by socket portion 14'. The needle should be oriented in a predetermined rotational position in relation to the shank, and more particularly it should project at right angles to the plane of handle 11. This rotational position is secured by the non-circular shape of socket portion 14' and the end portion of the needle having the flat faces 31, which fits into socket portion 14'. The end portion of the needle having the flat faces 31 joins the body of the needle over e conical portion 32, which tapers towards a shoulder 33.

10

20

25

30

An axial blind hole extends from the end surface of the needle said hole having a threaded portion 23 and inwardly thereof a narrower, cylindrical portion 24. Guide pin 19 is dimensioned to be guidingly received by said latter portion when the threaded portion 18 for attaching needle 21 to the rest of the surgical instrument is screwed into threaded portion 23 of the blind hole by rotating shaft 15 by manual rotation of knob 16, the end surfaces of the shank and the needle being pressed against each other. Also this attachment is in agreement with that described in PCT/SE95/00964.

When the method as described in PCT/SE95/00964 is practised two needles 21A and 21B, FIG. 6 of the embodiment described shall be connected one at each end of a tape 26. According to the present invention the tape of the preferred embodiment comprises a mesh or netting forming openings of the order of 1 mm. A suitable material for the tape is PROLENE®, a knitted polypropylene mesh having a thickness of 0,7 mm manufactured by Ethicon, Inc., Sommerville, New Jersey, USA. This material is approved by FDA in USA for implantation into the human body. The netting (tape) preferably has a width of approximately 10 mm and is enclosed in a thin polyethylene sheath 34 which in

WO 97/13465 PCT/SE96/01269

flattened condition has substantially the same width as the tape although a difference in width is shown in FIG 2 in order to make the provision of the sheath more clear. The length of the netting should be approximately 400 mm. The netting and the sheath are interconnected by means of two rows 35 of stiching. The end portion of the sheath is attached to the conical portion 32 of the needle by means of a suitable strong glue, and the interconnection of the needle and sheath is covered by a shrink hose 36 of rubber which extends from the shoulder 33 over the conical portion 32 and partly over the cylindrical end portion 30 of the needle. The shrink hose is substantially flush with the surface of the needle at the shoulder. By this arrangement the netting is securely attached to the needle.

The purpose of sheath 34 is above all to facilitate the insertion of the netting in the manner described in PCT/SE95/00964 i e when the netting is pulled at the ends thereof from the vaginal wall to the abdominal skin and to avoid that rough edges of the netting irritate or damage the body tissues.

15

20

30

35

When the tape has been positioned in the correct position as a sling around the urethra the polyethylene sheath shall be removed, and in order to facilitate the removal the sheath should be perforated at the longitudinal center thereof as indicated by a dot-and-dash line 37 in FIG. 6, so that the two halves of the sheath can be withdrawn from the body by pulling at the respective outer ends thereof the halves being separated at the perforation under the influence of the pulling force.

The purpose of the polyethylene sheath is also to protect the netting during attachment to the needles and during handling before and during insertion into the body.

The longitudinal center of the tape and sheath should be indicated by a visible colour mark 38, FIG. 6 so that the surgeon readily can see when the netting is sym-

metrically located with reference to urethra during the surgery.

20

CLAIMS

- 1. Surgical instrument for treating female urinary incontinence, comprising a shank (10) having a handle (11) at one end thereof, and two curved needle-like elements (21) which are each attached at one end thereof to one end of a tape (26) to be implanted into the body, and are constructed to be connected one at the time with the shank to form a curved portion at the other end end thereof each element being intended to be passed into the body via the anterior (suburethral) vaginal wall and being dimensioned to extend from the inside surface of the vaginal wall over the back of the pubic bone to the outside of the abdominal wall, c h a r a c t e r i z e d in that the tape comprises a netting (26) enclosed by a thin plastic sheath (34).
- 2. Instrument as in claim 1 c h a r a c t e r i z e d in that the netting (26) is made of polypropylene.
 - 3. Instrument as in claim 2 c h a r a c t e r i z e d in that the sheath (34) is made of polyethylene.
 - 4. Instrument as in any of claims 1 to 3 c h a r a c t e r i z e d in that the sheath (34) is perforated at the longitudinal center thereof.
 - 5. Instrument as in any of claims 1 to 4 characteristic charact
- 6. Instrument as in any of claims 1 to 5 c h a r a c t e r i z e d in that the needle-like element (21) comprises a non-circular end portion fitting into a non-circular socket (14') at said other end of the shank (10).
- 7. Instrument as in claim 6
 c h a r a r a c t e r i z e d in that said end portion of
 the needle-like element (21) joins the rest of the element
 by a conical portion (32) tapering towards a shoulder (33)
 on the needle-like element.

- 8. Instrument as in claim 7 c h a r a c t e r i z e d in that the netting (26) and the sheath (34) are connected to the needle-like element (21) by gluing to said conical portion (32).
- 9. Instrument as in claim 8 c h a r a c t e r i z e d in that the netting (26) and the sheath (34) at the site of attachement thereof are covered by a shrink hose (36).
- 10. Instrument as in claim 9 c h a r a c t e r i z e d in that one end of the shrink hose (36) abuts the shoulder (33) and is substantially flush with the surface of the needle-like element at said shoulder.
- 11. Instrument as in claim 9 or 11, c h a r a c t e r i z e d in that the netting (26) and the sheath (34) project from the shrink hose (36) at the other end thereof.
 - 12. Instrument as in any of claims 1 to 11, c h a r a c t e r i z e d in that a visable marking (38) is provided on the sheath (34) at the longitudinal center thereof.

20






FIG. 1


SUBSTITUTE SHEET




SUBSTITUTE SHEET




SUBSTITUTE SHEET





SUBSTITUTE SHEET



SUBSTITUTE SHEET

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 96/01269

A. CLASSIF	ICATION OF SUBJECT MATTER				
IPC6: A61B 17/04 According to International Patent Classification (IPC) or to both national classification and IPC					
B. FIELDS S	SEARCHED				
Minimum docur	mentation searched (classification system followed b	y classification symbols)			
IPC6: A61	В				
Documentation	searched other than minimum documentation to th	e extent that such documents are included in	the fields searched		
SE,DK,FI,	NO classes as above				
Electronic data l	base consulted during the international search (nam	e of data base and, where practicable, search	terms used)		
C. DOCUME	ENTS CONSIDERED TO BE RELEVANT				
Category* Cit	tation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.		
P S	E 503271 C2 (MEDSCAND AB), 29 (29.04.96)	April 1996			
A W	WO 9003766 A1 (P.E. PETROS), 19 April 1990 (19.04.90)				
A D	E 4334419 A1 (KLINIKUM DER ALBERT-LUDWIGS-UNIVERSITÄT I 13 April 1995 (13.04.95)	VIGS-UNIVERSITÄT FREIBURG.),			
	·				
A U:	US 5403328 A (SHALLMAN,R.W.), 4 April 1995 (04.04.95)				
		·			
Further do	ocuments are listed in the continuation of Box	C. X See patent family annex	•		
"A" document des	omes of cited documents fining the general state of the art which is not considered cular relevance	"I later document published after the inter date and not in conflict with the applic the principle or theory underlying the i	abon but cited to understand		
"E" criter document but published on or after the international filing date "L" document which may throw doubts on priority claims or which is cited to establish the publication date of another citation or other		"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone.			
"O" document rete means	n (as specified) erring to an oral disclosure, use, exhibition or other	"Y" document of particular relevance; the c considered to involve an inventive step combined with one or more other such	when the document is documents, such combination		
"P" document put the priority di	blished prior to the international filing date but later than ate claimed	heing obstous to a person skilled in the "&" document member of the same patent f			
Date of the actu	ual completion of the international search	Date of mailing of the international se	arch report		
5 March 1997		06.0397			
Name and mail	ling address of the ISA	Authorized officer			
Swedish Pate Box 5055, S-1	ent Office 02 42 STOCKHOLM	Anette Hall			
Facsimile No.	+ 46 8 666 02 86	Telephone No. + 46 8 782 25 00			

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/02/97

International application No.
PCT/SE 96/01269

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
SE-C2-	503271	29/04/96	AU-A- SE-A- WO-A-	3402495 9402872 9606567	22/03/96 01/03/96 07/03/96
WO-A1-	9003766	19/04/90	AT-T- AU-A- DE-D,T- EP-A,B- SE-T3- US-A-	119758 4406489 68921762 0437481 0437481 5112344	15/04/95 01/05/90 03/08/95 24/07/91 12/05/92
DE-A1-	4334419	13/04/95	NONE		
US-A-	5403328	04/04/95	CA-A- EP-A-	2094685 0567130	23/10/93 27/10/93

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

BLACK BORDERS

IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

FADED TEXT OR DRAWING

BLURRED OR ILLEGIBLE TEXT OR DRAWING

SKEWED/SLANTED IMAGES

COLOR OR BLACK AND WHITE PHOTOGRAPHS

GRAY SCALE DOCUMENTS

LINES OR MARKS ON ORIGINAL DOCUMENT

REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

☐ OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.